

Advanced Information



New KEF Home Theatre 2000 Series - KHT2005.3

The new KHT2005.3 is the latest version of KEF's most iconic home theatre system, first introduced to the market in 2000. A full 5.1 system complete with satellites, centre channel and the new KUBE-2 subwoofer. The satellites and centre channel have an improved multi-directional desktop mount with better stability and user preference positioning, while KUBE-2 provides a powerful performance, complimenting the clarity and sound quality of the satellites and centre channel.

This improved system retains the renowned 4 inch (100mm) Uni-Q[®], driver. Its metal dome tweeter and neodymium magnets deliver an extended bandwidth normally associated with much larger units. KEF Uni-Q technology disperses the sound over a much wider area for all to enjoy the moment without the loss of sound quality wherever they are sitting.

The new KUBE-2 subwoofer with a built-in Class-D 200W amplifier, can deliver a well defined and impressive bass complimenting the 2000 series satellites or any other home theatre system as the new subwoofer is also available separately. The KUBE-2 has a bass boost control which allows adjustment of the subwoofer response to compensate for room conditions and user preferences together with an impressive 10 inch (250mm) side-firing drive unit and matching ABR.

The KHT2005 was the first of the now iconic egg designs for KEF and has helped place the brand at the forefront of the home theatre market. Not only because of the breathtaking performance but also its stylish design has made it a great addition to any home theatre.

The new KHT2005.3 is finished in either matt silver or high gloss black.

Specifications

Satellite speakers

Model:	HTS2001.3 / HTC2001.3
Type:	Two-way bass relex Satellite/Centre
Drive units:	100mm (4in.) Uni-Q array with 19mm (0.75in.) aluminium HF
Frequency response ($\pm 3\text{dB}$):	80Hz - 27kHz
Crossover frequency:	3kHz
Power handling	100W
Sensitivity (2.83V/1m):	88dB
Maximum output (SPL):	104dB
Impedance:	8 Ω
Magnetic shielding:	Yes
Internal volume:	1.5litres
Net weight:	2.0kg (4.4lbs)
Dimensions (H x W x D):	Sat 228 x 130 x 150 mm (9.0 x 5.1 x 5.9 in.) Ctr 162 x 190 x 150 mm (6.4 x 7.5 x 5.9 in.)
Finish:	High gloss black, matt silver
Optional accessories:	Floorstand



Subwoofer

Model:	KUBE-2
Type:	Powered subwoofer
Drive unit:	1 x 250mm (10in.) + 1 x 250mm (10in.) ABR
Frequency response ($\pm 3\text{dB}$):	35Hz - 150Hz
Amplifier:	200W built-in Class-D
Maximum output (SPL):	112dB
Internal volume	23.0litres
Net weight:	12.0kg (26.5lbs)
Dimensions (H x W x D):	335 x 330 x 330 mm (13.2 x 13.0 x 13.0 in.)
Finish:	Black with gloss upper surface



GP Acoustics reserve the right, in line with continuous research and development, to amend or change specifications without prior notice. E. & O.E.

KEF[®]
INNOVATORS IN SOUND



GP Acoustics (UK) Ltd., Eccleston Road, Tovil, Maidstone, Kent, ME15 6QP U.K. Tel: + 44 (0)1622 672261 Fax: + 44 (0)1622 750653
GP Acoustics (US) Inc., 10 Timber Lane, Marlboro, New Jersey 07746 U.S.A. Tel: +(1) 732 683 2356 Fax: +(1) 732 683 2358
GP Acoustics GmbH, Heinrichstraße 51, D-44536 Lünen, Deutschland. Tel: +49 (0) 231 9860-320. Fax: +49 (0) 231 9860-330
GP Acoustics (France) SAS, 39 Rue des Granges Galand - BP60414, 37554 Saint Avertin CEDEX, France. Tel : +33(0)2 47 80 49 01 Fax : +33(0)2 47 27 89 64
GP Acoustics (HK) Limited, 6F, Gold Peak Building, 30 Kwai Wing road, Kwai Chung, N.T., Hong Kong. Tel: +85 (0) 2410 8188 Fax: +85 (0) 2401 0754

KEF and Uni-Q are registered trademarks. Uni-Q is protected under GB patent 2 236929, U.S. Pat. No. 5,548,657 and other worldwide patents. KEF reserve the right, in line with continuing research and development, to amend or change specifications.

www.kef.com